

Characterization of the main instability mechanisms in sessile droplet evaporation

Marc Medale, Sergey Semenov, David Brutin

▶ To cite this version:

Marc Medale, Sergey Semenov, David Brutin. Characterization of the main instability mechanisms in sessile droplet evaporation. 3rd International Conference on Droplets, Jul 2017, Los Angeles, United States. hal-01793952

HAL Id: hal-01793952 https://amu.hal.science/hal-01793952v1

Submitted on $17~\mathrm{May}~2018$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Characterization of the main instability mechanisms in sessile droplet evaporation

Marc Medale¹, Sergey Semenov², David Brutin¹

¹ Aix-Marseille Université, CNRS, IUSTI UMR 7343, Technopôle de Chateau-Gombert, 13013 Marseille, France ² Aix-Marseille Université, CNRS, MADIREL UMR 7246, Campus de Saint Jérôme, 13013 Marseille, France

E-mail: marc.medale@univ-amu.fr

While the involved physical phenomena are nowadays properly understood, sessile droplet evaporation remains an active research area since several experiments are not comprehensively explained. Indeed, recent experimental works have provided very interesting dynamics [1-5], whose characteristics strongly depend on control parameters, such as substrate temperature, ambient pressure and the various thermo-physical properties of substrate, droplet liquid and surrounding gas. There is no general agreement in the scientific community about the root-causes of the observed behavior. Are they hydro-thermal waves, Rayleigh-Bénard-Marangoni instabilities, or even something else?

One of the means to unmistakably answer this question would consist in conducting a stability analysis of the fully coupled and transient fluid flow, heat and mass transfer problem [6]. However, to do so, one must first overcome two major difficulties. The first one concerns the computation of the transient base state, whose complexity arises from the strong non-linearities associated with the three competing drivina mechanisms: i) Stefan flow draining liquid towards the interface and more specifically to the triple line when the latter is pinned; ii) buoyancy in the liquid and vapor inducing thermo-solutal convection; iii) surface tension gradient along the liquid-gas interface inducing thermo-soluto-capilary convection. The second level of complexity to perform a relevant stability analysis consists in the intrinsic unsteadiness of the sessile drop evaporation process, in which several time scales co-exist.

For particular evaporation configurations, the dynamics of perturbations lies in a much shorter time scale than the total evaporation time, so in this case one can separate perturbations from the base state in a frozen time approach. This enabled us to find that the prevalent perturbations of the base state mainly come from the liquid droplet in which they trigger tridimensional flow structures. Therefore, we have then conducted 3D computations restricted to the droplet and its substrate with a one-sided model, in which heat and mass transfer across the liquid-gas interface is modeled in a semi-analytical way. These unsteady computations are performed during the first stage of the evaporation process in which the triple line is pinned to the substrate, so that the droplet diameter is kept constant, meanwhile the contact angle continuously decreases over time. The obtained results are in good

agreement against several experiments performed either under terrestrial conditions or reduced gravity (parabolic flights), cf. figure 1.



Figure 1 - 3D unsteady computations: thermal and velocity fields over the droplet surface and in a cut plane.

These one-sided model computations helped us to understand one of the potential instability scenarios. At the beginning, a torus roll appears in the wedge close to the pinned triple line and drives eventually an inner roll by viscous stress depending on the droplet aspect ratio (height/radius). As their intensity increases over time they split into thermo-capillary cells owing to Rayleigh-Bénard-Marangoni instability. Then, the number of cells evolves in time owing to the fact that the plane wavelength of these cells is closely related to their depth. As in the first stage of droplet evaporation the triple line is pinned the wetting angle consequently decreases, so does the liquid height, changing correspondingly the thermal Bond number (ratio of Rayleigh to Marangoni numbers). As the number of thermo-convective cells changes over time. hydro-thermal waves take place to redistribute the internal energy in the droplet. In the second stage of evaporation the droplet diameter continuously decreases, so does its perimeter, while the wetting angle stays roughly constant. Therefore the height of peripheral cells remains also constant; consequently their number has to decrease in order to match the droplet perimeter. Here again, hydro-thermal waves enter the game to redistribute the internal energy in the droplet.

The dark side of this approach is that computing times are still prohibitive to perform any parametric study this way. Therefore we have conducted a dimensional analysis to account for the main physical components of the problem. As usual, one assumes perturbations been able to destabilize the base state provided their energy reaches a certain amount of the total energy of the system, made-up of the liquid droplet and its surrounding gas (air + liquid vapor). To approximate these energy levels, prevalent terms have to be evaluated. In terrestrial conditions the two prevalent driving terms are buoyancy (thermal and solutal) together with surface tension gradients (thermo and soluto-capillary forces). The first one can be quantified thanks to thermal and solutal Rayleigh numbers, meanwhile the second one can be quantified by thermal and solutal Marangoni numbers. On the other hand, the energy involved in the evaporation process is related to the vapor flux throughout the droplet interface times the latent heat of vaporization. Therefore, a linear combination of all these terms enables to quantify the total energy involved in the evaporation process. Computing the latter in various experiments where instabilities have been either observed or not (cf. figure 2), enabled us to empirically determine a threshold of instability occurrence.



Figure 2 – Top view images from infra-red camera of sessile drop evaporation revealing somehow their internal flow patterns (same thermal conditions but different fluids and gravity levels).

This semi-empirical analysis enables us to discern instances of instability depending on experimental sets of parameters. However, some further work has to be performed to improve the described model in order to become predictable.

Acknowledgements. The authors acknowledge the French spatial agency (CNES) for funding support: parabolic flight experiments and second author's post-doc.

References

[1] K. Sefiane, A. Steinchen, R. Moffat. On hydrothermal waves observed during evaporation of

sessile droplets. *Colloids&Surfaces A*, 365 (2010) 95–108.

[2] D. Brutin, B. Sobac, F. Rigollet, C. Le Niliot. Infrared visualization of thermal motion inside a sessile drop deposited onto a heated surface. *Exp. Therm. Fluid Sci.*, 35 (2011) 521–530.

[3] B. Sobac, D. Brutin. Thermocapillary instabilities in an evaporating drop deposited onto a heated substrate. *Phys. Fluids*, 24 (2012) 032103.

[4] F. Carle, B. Sobac, D. Brutin. Hydrothermal waves on ethanol droplets evaporating under terrestrial and reduced gravity levels. *J. Fluid Mech.*, 712 (2012) 614–623.

[5] G. Karapetsas, O.K. Matar, P. Valluri, K. Sefiane. Convective Rolls and Hydrothermal Waves in Evaporating Sessile Drops. *Langmuir*, 28 (2012) 11433–11439.

[6] H.A. Dijkstra, F.W. Wubs, A.K. Cliffe, E. Doedel, I.F. Dragomirescu, B. Eckhardt, A.Y. Gelfgat, A.L. Hazel, V. Lucarini, A.G. Salinger, E.T. Phipps, J. Sanchez-Umbria, H. Schuttelaars, L.S. Tuckerman, U. Thiele. Numerical Bifurcation Methods and their Application to Fluid Dynamics: Analysis beyond Simulation. *Commun. Comput. Phys.*, 15 (2014) 1–45.