



## Lifetime of inkjet printing OPV modules for indoor applications.

Hasan Alkhatib, Marcel Pasquinelli, Ludovic Escoubas, Jean Jacques Simon,  
Pascal Pierron, Sadok Ben Dkhil

### ► To cite this version:

Hasan Alkhatib, Marcel Pasquinelli, Ludovic Escoubas, Jean Jacques Simon, Pascal Pierron, et al.. Lifetime of inkjet printing OPV modules for indoor applications.. 36th European PV Solar Energy Conference and Exhibition (EU PVSEC 2019), Sep 2019, Marseille, France. . hal-02289308

HAL Id: hal-02289308

<https://amu.hal.science/hal-02289308>


Submitted on 17 Sep 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Introduction

Harvesting energy from their environment could be an ideal solution for an autonomous function of numerous small electronics. Organic Photovoltaic (OPV) cells are a promising technology for next generation photovoltaic cells combining novel properties such as light weight, flexibility, or color design with large-scale manufacturing with low environmental impact. Furthermore, the OPV cells are good solution for Indoor applications. In this field, DRACULA TECHNOLOGIES (DT) has developed inkjet printing organic solar cells and modules. The great advantage of inkjet printing as a digital technology is the freedom of forms and designs, large area organic modules with different artistic shapes. The stability of OPV cells are critical element for up-scaling and commercialization of this technology. To evaluate the stability and lifetime of the DT modules, the ISOS-D-1 (shelf lifetime) protocol is applied for 175 days. The devices were stored under dark ambient conditions and a LED light source is used for the periodical characterizations.





## Test bench (module & light source specifications)




LED ceiling lamp  
(2100 lm, 6500 K, 17 W)

Structure	Layers	Encapsulation	Filtre UV	Substrat	Cell number	Configuration	Active area	Illumination level	Efficiency % at the 1st characterization (time = 0)
Inverted	PET/ITO/AZO/ Active Layer/ PEDOT-PSS/Ag	Low film barrier properties ( $10^{-1}$ $\text{g}/\text{m}^2/\text{d}$ )	---	Flexible	6	Serial	$8 \text{ cm}^2$	200 lx	3,24 %




## Results

Temperature and relative humidity evolution during the storage phases (from 25 jan. 2019 to 19 july 2019).




Degradation curves of efficiency (normalized to the initial value at time = 0) for 3 illumination levels.




$T_{80}$  : Time for the efficiency to decrease to 80% of the initial value at time = 0.

Illumination level	$T_{80}$
200 lx	118 days
500 lx	66 days
1000 lx	20 days


Degradation curves of  $I_{sc}$  (normalized to the initial value at time = 0) for 3 illumination levels.




Degradation curves of  $V_{oc}$  (normalized to the initial value at time = 0) for 3 illumination levels.




Degradation curves of the fill factor (normalized to the initial value at time = 0) for 3 illumination levels.



Degradation curves of  $P_{max}$  ( $\mu\text{W}$ ) for 3 illumination levels.



LBIC (Light Beam Induced Current) mapping (in 2D and 3D) of the presented module at time = 175 days.



Acknowledgement : We acknowledge Dr. Damien BARAKEL (IM2NP IRM-PV) for his contribution in the LBIC mapping.